

ALLOY PROTECTOR

Page: 1

Compilation date: 22/01/2013

**Revision date:** 03/02/2015

Revision No: 3

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: ALLOY PROTECTOR

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Company name: Tribos Coatings (International) Ltd

Rossland House, Headlands Business Park

Salisbury Road

Ringwood

Hants

BH24 3PB

**Tel:** +44(0)1425 470850

**Fax:** +44(0)1425 470853

Email: info@triboscoatings.com

# 1.4. Emergency telephone number

Emergency tel: +44(0)1425 470850

(office hours only)

# **Section 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification under CHIP: -: R10

Classification under CLP: Flam. Liq. 3: H226

Most important adverse effects: Flammable.

# 2.2. Label elements

Label elements under CLP:

Hazard statements: H226: Flammable liquid and vapour.

Signal words: Warning

Hazard pictograms: GHS02: Flame



Precautionary statements: P243: Take precautionary measures against static discharge.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water.

# ALLOY PROTECTOR

Page: 2

P280: Wear protective gloves.

P370+378: In case of fire: Use dry powder for extinction. P403+235: Store in a well-ventilated place. Keep cool.

P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP:

**Hazard symbols:** Symbol not required. **Risk phrases:** R10: Flammable.

### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

#### 3.2. Mixtures

# Hazardous ingredients:

### PROPAN-2-OL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-661-7	67-63-0	F: R11; Xi: R36; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	1-10%
			STOT SE 3: H336	

Contains: Propan-2-ol (CAS No: 67-63-0)

# Section 4: First aid measures

### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

# 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

# Section 5: Fire-fighting measures

### ALLOY PROTECTOR

Page: 3

# 5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire

brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side

up to prevent the escape of liquid.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

## 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of

the area. Avoid the formation or spread of mists in the air.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

### 7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

# 8.1. Control parameters

### ALLOY PROTECTOR

Page: 4

### Hazardous ingredients:

#### PROPAN-2-OL

### Workplace exposure limits:

### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m3 (400ppm)	1250 mg/m3 (500ppm)	-	-

# **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid Colour: Cream

Odour: Characteristic odour

Boiling point/range°C: >35 Flash point°C: 42

Relative density: 1

### 9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

# 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

# 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

# ALLOY PROTECTOR

Page: 5

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

# **Hazardous ingredients:**

#### **PROPAN-2-OL**

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

Toxicity values: No data available.

#### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

# **Section 12: Ecological information**

# 12.1. Toxicity

Ecotoxicity values: No data available.

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

# 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

# 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

# 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

# 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

# ALLOY PROTECTOR

Page: 6

# **Section 13: Disposal considerations**

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

#### 14.1. UN number

UN number: UN1139

# 14.2. UN proper shipping name

Shipping name: COATING SOLUTION

### 14.3. Transport hazard class(es)

Transport class: 3

# 14.4. Packing group

Packing group: III

### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

# 14.6. Special precautions for user

Special precautions: No special precautions.

**Tunnel code:** D/E **Transport category:** 3

# **Section 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

# **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour. H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

# ALLOY PROTECTOR

Page: 7

R10: Flammable.

R11: Highly flammable.

R36: Irritating to eyes.

R67: Vapours may cause drowsiness and dizziness.

**Legend to abbreviations:** PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.